

**MULTI UTILITY TRICYCLE**  
**TD 2 C 79**



**Dimensions & Specifications :**

Product Code	-	TD 2 C 79
Overall length	-	2225 ± 50 mm
Overall width	-	985 ± 50 mm
Overall Height	-	1780 ± 50 mm

**Special Features :**

- Use of special quality cold drawn and bright-annealed tubes conforming to IS:2039 makes the main frame sturdy to withstand stresses caused by tough terrain. Neatly welded joints and further to the strength of main frame.
- Cushioned seat and backrest provide desired comfort to the user. Seat can accommodate two persons in case of need.
- Driven by standard chain and sprocket mechanism. The selection of gear ratio ensures max. Mechanical advantage using minimum effort. Can be driven by right or left hand. Provision of chain adjustment on either side.
- The steering rod serves dual function of directional control as well as broking. Handgrip on the steering rod is specially made of non-marking type rubber and designed for longer life.
- The raw materials and bought-outs used in manufacture of Tricycle are of tested quality conforming to relevant specifications laid down by BIS.
- Self-drying points of repute, impart excellent overall finish.
- The unit is provided with suitable metal plate side guards fitted on the Al. Alloy Extruded vertical tubular support pipes.
- The unit has a suitable polyester fabric (tetron or equiv.) canopy for safety from excessive sun light / rain & other weather hazards and is also fitted with a suitable box fitted on the rear portion of the tricycle for safe keeping of the PCO unit / instruments / other items.